

CLARENCE STREAM SOUTH ZONE DRILL RESULTS

Hole ID	From (m)	To (m)	Intercept (m)	TW (m)	Au g/t	Au Cut g/t	Azimuth	Dip	UTM		Total Depth (m)	
									Easting	Northing		
GWM-16CS-331	215.00	216.00	1.00	1.00	0.8		147°	-54°	658089	5023925	402	
	258.25	259.05	0.80	0.80	0.8							
	332.40	338.40	6.00	6.00	2.1							
including	332.40	333.40	1.00	1.00	6.3							
GWM-16CS-332	170.20	171.20	1.00	1.00	3.7		145°	-60°	658149	5023920	399	
	304.75	305.75	1.00	1.00	1.9							
	329.50	330.00	0.50	0.50	2.5							
GWM-16CS-333	211.20	211.80	0.60	0.60	1.1		140°	-47°	658166	5023990	396	
	213.00	213.80	0.80	0.80	2.6							
	291.45	291.95	0.50	0.50	3.8							
	351.75	352.25	0.50	0.50	1.4							
	366.50	367.00	0.50	0.50	1.2							
	372.00	373.00	1.00	1.00	1.5							
GWM-16CS-334	379.46	381.70	2.24	1.60	1.1		158°	-71°	658089	5023933	453	
GWM-16CS-335	201.00	211.00	10.00	9.30	0.9		145°	-53°	658141	5023797	252	
GWM-16CS-336	301.25	302.25	1.00	0.90	20.0		138°	-53°	658021	5023840	340	
GWM-16CS-337	84.00	84.50	0.50	0.48	1.4		151°	-52°	658403	5023848	186	
	141.80	143.80	2.00	1.90	1.6							
GWM-16CS-338	331.30	336.80	5.50	5.20	5.5		143°	-50°	659024	5024498	402	
	including	335.30	336.80	1.50	1.42	13.2						
		350.90	351.55	0.65	0.61	2.4						
GWM-16CS-339	349.12	349.72	0.60	0.50	2.8		162°	-71°	659091	5024482	399	
GWM-16CS-340	264.00	273.00	9.00	7.40	1.4		146°	-66°	659032	5024383	300	
GWM-16CS-341	151.80	152.80	1.00	0.90	2.1		135°	-62°	657883	5023687	240	
	156.80	157.80	1.00	0.90	9.0							
GWM-16CS-342	No significant values							145°	-55°	657871	5023603	200
GWM-16CS-343	33.00	63.00	30.00	29.10	4.6*		145°	-45°	658305	5023694	180	
	including	33.00	47.00	14.00	13.58	8.9**						
	includes	33.00	34.00	1.00	0.97	28.0						
	includes	38.00	39.00	1.00	0.97	20.7						
	includes	45.00	46.00	1.00	0.97	32.1						
GWM-16CS-344	28.00	51.00	23.00	22.30	4.3*		145°	-45°	658286	5023677	100	
	including	29.00	45.00	16.00	15.51	5.6**						
	includes	30.00	31.00	1.00	0.96	21.4						
	includes	35.00	37.00	2.00	1.94	13.6						
GWM-16CS-345	17.00	41.00	24.00	23.20	4.6*		145°	-45°	658293	5023669	51	
	including	19.00	27.00	8.00	7.70	9.6**						
	includes	19.00	20.00	1.00	1.00	12.1						
	includes	20.00	21.00	1.00	1.00	10.4						
	includes	21.00	22.00	1.00	1.00	16.3						
	includes	25.00	26.00	1.00	1.00	12.5						
	includes	26.00	27.00	1.00	1.00	15.6						
	includes	30.00	31.00	1.00	1.00	8.6						
GWM-16CS-346	15.00	46.00	31.00	29.90	10.0*	6.6	145°	-45°	658331	5023680	51	
	including	15.00	27.00	12.00	11.60	24.2**						15.3
	includes	15.00	16.00	1.00	1.00	55.8						30.0
	includes	16.00	17.00	1.00	1.00	5.6						
	includes	17.00	18.00	1.00	1.00	9.0						
	includes	18.00	19.00	1.00	1.00	10.4						
	includes	19.00	20.00	1.00	1.00	20.5						
	includes	20.00	21.00	1.00	1.00	8.1						
	includes	23.00	24.00	1.00	1.00	13.0						
	includes	24.00	25.00	1.00	1.00	59.2						30.0
	includes	25.00	26.00	1.00	1.00	81.7						30.0
includes	26.00	27.00	1.00	1.00	25.2							
GWM-16CS-347	23.00	41.00	18.00	17.40	7.9*	5.6	145°	-45°	658269	5023658	51	
	including	23.00	27.00	4.00	3.90	30.1**						19.7
	includes	23.00	24.00	1.00	1.00	50.6						30.0
	includes	24.00	25.00	1.00	1.00	7.2						
	includes	25.00	26.00	1.00	1.00	11.6						

CLARENCE STREAM SOUTH ZONE DRILL RESULTS

Hole ID	From (m)	To (m)	Intercept (m)	TW (m)	Au g/t	Au Cut g/t	Azimuth	Dip	UTM		Total Depth (m)	
									Easting	Northing		
Includes	26.00	27.00	1.00	1.00	50.8	30.0						
GWM-16CS-348	165.00	178.00	13.00	12.20	10.1*	4.1	154°	-50°	658184	5023769	198	
including	165.00	170.00	5.00	4.70	24.9**	9.3						
includes	165.00	166.00	1.00	0.90	108.0	30.0						
includes	168.00	169.00	1.00	1.00	6.8							
GWM-16CS-349	194.25	207.00	12.75	10.20	2.1	2.1	151°	-63°	658184	5023769	213	
including	194.25	196.25	2.00	1.60	7.5	7.5						
GWM-16CS-350	Appears to have stopped short of the target on the Gabbro contact; it will be extended.							145°	-56°	658115	6023783	228
GWM-16CS-351	72.00	79.00	7.00	6.20	1.1	1.1	145°	-53°	658161	5023810	252	
including	78.00	79.00	1.00	0.90	3.5	3.5						
	180.10	180.60	0.50	0.40	9.7	9.7						
	221.25	226.66	5.40	4.80	5.0	5.0						
	221.75	222.40	0.65	0.60	29.0	29.0						
GWM-17CS-355	44.00	45.00	1.00	1.00	1.2		145°	-45°	658290	5023785	201	
	110.00	153.00	43.00	42.20	0.7							
including	117.00	118.00	1.00	1.00	8.3							
including	129.50	130.50	1.00	1.00	2.3							
including	149.00	150.00	1.00	1.00	3.3							
GWM-17CS-356	65.50	66.50	1.00	1.00	2.0		145°	-45°	658324	5023729	210	
	89.00	91.75	2.75	2.70	2.1							
GWM-17CS-357	56.00	57.00	1.00	1.00	2.4		145°	-45°	658351	5023728	222	
	150.00	153.00	3.00	2.90	0.8							
GWM-17CS-358	13.10	19.00	5.90	5.70	17.4	16.3	145°	-45°	658329	5023690	171	
including	14.10	17.25	3.15	3.10	31.4	29.8						
	47.00	54.50	7.50	7.30	1.1							
including	53.00	53.50	0.50	0.50	4.1							
	60.00	65.50	5.50	5.30	2.5							
	114.00	115.00	1.00	1.00	1.2							
GWM-17CS-359	42.60	43.60	1.00	1.00	1.2		145°	-45°	658237	5023685	118	
	50.00	62.00	12.00	11.70	7.6	6.8						
including	56.65	58.45	1.80	1.70	41.8	36.5						
GWM-17CS-360	103.35	115.75	12.40	12.00	11.8	6.6	145°	-45°	658208	5023727	171	
including	103.35	104.50	1.15	1.00	105.0	40.0						
GWM-17CS-361	62.00	63.00	1.00	1.00	1.7		145°	-45°	658193	5023655	120	
GWM-17CS-362	61.25	64.45	3.20	3.10	11.6		145°	-45°	658181	5023677	120	
including	61.25	62.45	1.20	1.20	26.8							
GWM-17CS-363	130.00	132.75	2.75	2.50	3.6		145°	-55°	658066	5023715	186	
including	130.75	131.75	1.00	0.90	7.6							
GWM-17CS-364	No significant values							140°	-45°	658401	5023795	150
GWM-17CS-365	26.00	38.00	12.00	11.60	1.0		143°	-45°	658509	5023767	102	
including	34.00	35.00	1.00	1.00	2.6							
GWM-17CS-366	17.50	32.60	15.10	14.60	6.1	4.2	142°	-55°	658468	5023742	102	
including	21.30	23.60	2.30	2.20	27.3	15.0						
	30.00	31.00	1.00	1.00	8.6							
GWM-21CS-368	16.60	17.20	0.60	0.60	0.5		136	-53	657975	5023548	150	
	31.30	36.00	4.70	4.60	3.6							
including	33.00	33.50	0.50	0.50	9.1							
including	34.00	35.00	1.00	1.00	8.5							
	83.60	84.50	0.90	0.90	0.9							
	97.50	98.00	0.50	0.50	0.7							
	100.40	114.00	13.60	13.20	1.7							
including	100.40	101.50	1.10	1.10	7.4							
including	107.60	108.30	0.70	0.70	4.9							
including	112.70	113.30	0.60	0.60	4.8							
	116.50	118.00	1.50	1.50	0.7							

CLARENCE STREAM SOUTH ZONE DRILL RESULTS

Hole ID	From (m)	To (m)	Intercept (m)	TW (m)	Au g/t	Au Cut g/t	Azimuth	Dip	UTM		Total Depth (m)
									Easting	Northing	
	134.50	135.00	0.50	0.50	0.5						
GWM-21CS-369	42.00	46.85	4.85	4.30	0.8		155	-64	657970	5023544	201
including	44.00	44.65	0.65	0.60	1.7						
	104.00	104.50	0.50	0.40	1.2						
	114.00	116.50	2.50	2.20	0.9						
	132.00	133.50	1.50	1.30	2.3						
GWM-21CS-370	37.50	38.50	1.00	0.90	0.5		155	-51	657970	5023544	180
	78.50	79.00	0.50	0.50	3.0						
	102.20	105.00	2.80	2.70	0.5						
GWM-21CS-371	26.50	27.00	0.50	0.50	2.6		140	-49	657952	5023591	201
	76.50	77.00	0.50	0.50	0.6						
	79.50	80.50	1.00	1.00	0.6						
	133.50	135.50	2.00	2.00	5.8						
	152.00	152.60	0.60	0.60	7.8						
GWM-21CS-372	51.50	52.50	1.00	1.00	1.7		150	-52	657984	5023613	219
	74.00	74.50	0.50	0.50	0.6						
	111.00	116.00	5.00	4.80	2.1						
including	114.00	115.00	1.00	1.00	6.3						
GWM-21CS-373	15.50	16.00	0.50	0.50	1.3		145	-55	658031	5023586	201
	75.00	79.50	4.50	4.30	1.1						
including	78.00	78.50	0.50	0.50	4.2						
	84.50	85.00	0.50	0.50	0.4						
GWM-21CS-374	87.00	88.00	1.00	1.00	0.5		150	-50	658020	5023700	183
	100.50	102.00	1.50	1.40	0.5						
	129.50	130.50	1.00	1.00	0.6						
	137.00	158.50	21.50	20.80	0.9						
including	138.00	139.00	1.00	1.00	5.3						
including	148.00	149.00	1.00	1.00	5.8						
including	153.00	154.00	1.00	1.00	3.2						
	178.50	181.50	3.00	2.90	19.0	11.3					
including	179.50	180.00	0.50	0.50	106.0	60.0					
GWM-21CS-375	15.50	17.00	1.50	1.50	0.8		141	-45	658040	5023750	210
	82.00	82.50	0.50	0.50	0.8						
	103.50	105.00	1.50	1.50	0.4						
	113.50	114.20	0.70	0.70	2.1						
	118.00	119.50	1.50	1.50	0.9						
	173.80	179.50	5.70	5.70	8.4						
including	173.80	174.50	0.70	0.70	29.3						
including	174.50	175.00	0.50	0.50	14.0						
including	175.50	176.00	0.50	0.50	18.0						
	189.50	190.00	0.50	0.50	1.5						
	201.50	202.00	0.50	0.50	0.7						
	205.50	206.00	0.50	0.50	0.9						
GWM-21CS-376	77.20	78.00	0.80	0.80	0.7		144	-45	658060	5023630	207
	82.50	85.10	2.60	2.60	2.8						
including	83.70	84.50	0.50	0.50	7.5						
	89.00	90.00	1.00	1.00	0.7						

CLARENCE STREAM SOUTH ZONE DRILL RESULTS

Hole ID	From (m)	To (m)	Intercept (m)	TW (m)	Au g/t	Au Cut g/t	Azimuth	Dip	UTM		Total Depth (m)
									Easting	Northing	
	100.00	100.50	0.50	0.50	1.0						
	103.50	104.80	1.30	1.30	1.1						
	121.00	122.50	1.50	1.50	0.6						
	125.00	125.50	0.50	0.50	1.6						
	192.50	193.00	0.50	0.50	0.5						

*Intersects are calculated with a 0.5 g/t Au bottom cut. **Intersects are calculated with a 3.0 g/t Au bottom cut.